



### Split Head/Super Plastic Key Benefits:



**SUPER PLASTIC SPLIT HEAD HAMMER**

Cast Iron head with Super Plastic faces.

The split Cast Iron Heads have two socket head cap screws to secure both handle and faces.

The design of the head allows for quick adjustment or replacement of both handle and faces.

The interchangeable faces provide a variety of striking options to suit most needs.

Also available with Rawhide or Nylon faces.

Faces are designed to wear, can be rotated for even wear and are easily and quickly replaceable.

Used as a heavy duty multi purpose soft faced hammer in most industries for assembly, repair and maintenance etc.

Sizes 5L and 9 also available with Fibreglass (FG) handles.

Reference	Size	Description	Round Head Diameter	Round Head Length	Square Head Dimension	Square Head Length	Approximate Weight	Approximate Length	Hardness	Spare Faces
35-SPH125	1	Split Head Hammer - Super Plastic Faces	32 mm 1.1/4 ins				630 g	280 mm 11 ins		77-910SPF
35-SPH150	2	Split Head Hammer - Super Plastic Faces	38 mm 1.1/2 ins				925 g	305 mm 12 ins		77-912SPF
35-SPH175	3	Split Head Hammer - Super Plastic Faces	44 mm 1.3/4 ins				1520 g	325 mm 12.3/4 ins		77-914SPF
35-SPH200	4	Split Head Hammer - Super Plastic Faces	50 mm 2 ins				2020 g	350 mm 13.3/4 ins		77-916SPF
35-SPH275	5	Split Head Hammer - Super Plastic Faces	70 mm 2.3/4 ins				3550 g	400 mm 15.3/4 ins		77-922SPF
35-SPH275FG	5FG	Split Head Hammer - Super Plastic Faces Fibreglass (FG) Handle	70 mm 2.3/4 ins				3950 g	920 mm 36 ins		77-922SPF
35-SPH275L	5L	Split Head Hammer - Super Plastic Faces	70 mm 2.3/4 ins				3950 g	920 mm 36 ins		77-922SPF
35-SPH400	9	Split Head Hammer - Super Plastic Faces	100 mm 4 ins				5200 g	920 mm 36 ins		77-400SPF
35-SPH400FG	9FG	Split Head Hammer - Super Plastic Faces Fibreglass (FG) Handle	100 mm 4 ins				5200 g	920 mm 36 ins		77-400SPF

### Split Head/Nylon Key Benefits:



**NYLON FACED SPLIT HEAD HAMMER**

Cast Iron head with Nylon faces.

The split Cast Iron Heads have two socket head cap screws to secure both handle and faces.

The design of the head allows for quick adjustment or replacement of both handle and faces.

The interchangeable faces provide a variety of striking options to suit most needs.

Also available with Rawhide or Super Plastic faces.

Faces are designed to wear, can be rotated for even wear and are easily and quickly replaceable.

Used as a heavy duty multi purpose soft faced hammer in most industries for assembly, repair and maintenance etc.

Reference	Size	Description	Round Head Diameter	Round Head Length	Square Head Dimension	Square Head Length	Approximate Weight	Approximate Length	Hardness	Spare Faces
36-NH125	1	Split Head Hammer - Nylon Faces	32 mm 1.1/4 ins				630 g	280 mm 11 ins		Nylon 76-125NF
36-NH150	2	Split Head Hammer - Nylon Faces	38 mm 1.1/2 ins				925 g	305 mm 12 ins		Nylon 76-150NF
36-NH175	3	Split Head Hammer - Nylon Faces	44 mm 1.3/4 ins				1520 g	325 mm 12.3/4 ins		Nylon 76-175NF
36-NH200	4	Split Head Hammer - Nylon Faces	50 mm 2 ins				2020 g	350 mm 13.3/4 ins		Nylon 76-200NF
36-NH275	5	Split Head Hammer - Nylon Faces	70 mm 2.3/4 ins				3550 g	400 mm 15.3/4 ins		Nylon 76-275NF

**THORACE DEAD BLOW NYLON HAMMER**

Coated Die cast Aluminium alloy head, Rubber grip and Nylon faces.

The Die cast Aluminium alloy head is fitted with screw in white Nylon faces or for certain specialist applications Brown Polyurethane.

A cavity inside the head is partially fitted with steel shot which adds to the weight, prevents rebound and delivers 'dead' blows of maximum force.

Faces are colour coded and can easily be replaced by hand.

Faces are designed to wear and are replaceable by hand.

Used, due to the easily interchangeable faces, as a multi purpose striking tool and is ideal for sustained and effective blows without recoil.

Commonly used in most assembly/fitting applications including engineering, toolmaking, shopfitting, partitioning, double glazing etc.



### Dead Blow/Nylon Key Benefits

Reference	Size	Description	Round Head Diameter	Round Head Length	Square Head Dimension	Square Head Length	Approximate Weight	Approximate Length	Hardness	Spare Faces
20-1010		Thorace Dead Blow Nylon Hammer	32 mm 1.1/4 ins				550 g	275 mm 11 ins		Tough Brown 76-710TF Hard White 76-710NF
20-1212		Thorace Dead Blow Nylon Hammer	38 mm 1.1/2 ins				700 g	305 mm 12 ins		Tough Brown 76-712TF Hard White 76-712NF
20-1414		Thorace Dead Blow Nylon Hammer	44 mm 1.3/4 ins				900 g	310 mm 12.1/4 ins		Tough Brown 76-714TF Hard White 76-714NF
20-1616		Thorace Dead Blow Nylon Hammer	50 mm 2 ins				1150 g	325 mm 12.3/4 ins		Tough Brown 76-716TF Hard White 76-716NF
20-2020		Thorace Dead Blow Nylon Hammer	63 mm 2.1/2 ins				1850 g	370 mm 14.1/2 ins		Tough Brown 76-720TF Hard White 76-720NF



## 950

**GUMMIHAMMER, DIN 5128 A**  
RUBBER HAMMER, DIN 5128 A

Eschenstiel ash handle

Art.-No.	Ø mm	l mm	g	📦
9500550	55	330	510	1
9500650	65	340	717	1
9500750	75	370	1005	1

## 710

**KUNSTSTOFF-HAMMER**  
PLASTIC FACED HAMMER

Eschenstiel lackiert mit austauschbaren Köpfen  
schlagfestes Cellulose-Acetat  
lacquered ash handle with replaceable heads  
shatterproof Cellulose-Acetate

Art.-No.	Ø mm	l mm	g	📦
7102700	27	265	233	4
7103200	32	280	331	4
7104000	40	320	557	4
7105000	50	340	862	1
7106000	60	376	1332	1



Art.-No.	Ø mm	l mm	g	📦
9950540	54	330	284	2
9950640	64	340	556	2
9950740	74	390	802	2
9950900	90	370	1186	2



## 706

**RÜCKSCHLAGFREIER SCHÖNHAMMER**  
RECOIL FREE SOFT FACED HAMMER

mit Stahlrohr-Stiel und Kunststoffgriff  
rückschlagfrei durch Stahlschrot im Kopfholmraum  
bis zu 100% höhere Schlagwirkung gegenüber normalen Schönhammern  
spaltfrei und verschleißfest  
Kunststoff-Köpfe nicht austauschbar für gesundheitsschonendes Arbeiten

with steel tube handle and plastic handle  
shock absorbing effect through steel shot in the head  
up to 100% higher impact effect than normal Soft Faced Hammers  
shatterproof and wear resistant  
plastic heads not interchangeable for safer working


Art.-No.	Ø mm	l mm	g	📦
9298710	35	305	646	1

## 720

**ERSATZKOPF**  
SPARE HEAD

für Kunststoff-Hammer Nr. 710  
schlagfestes Cellulose-Acetat  
for Plastic Faced Hammer No. 710  
shatterproof Cellulose-Acetate

Art.-No.	Ø mm	g	📦
7202700	27	15	10
7203200	32	29	10
7204000	40	40	10
7205000	50	68	5



MARTELO SEM RICOCHETE

COD.	lb	L (mm)	Ø A (mm)	B (mm)	📦
69748	0,5	275	40	80	
69750	1,5	325	50	110	6
69752	3	360	60	130	
69753	4	425	65	140	
69754	5	430	70	150	3
69755	6		75	165	



## 936

**GUMMIAUFSATZ FÜR HANDFÄUSTEL**  
RUBBER ATTACHMENT FOR MINING SLEDGE HAMMER

Gummi Rubber

Art.-No.	g	g	📦
9295240	1000	400	1
9295250	1250	400	1
9295260	1500	400	1
9295270	2000	400	1

## 983

**PLATTENLEGERHAMMER, DIN 6475**  
PAVER'S HAMMER, DIN 6475

VPA-G5 geprüft  
Hammerkopf geschmiedet  
Eschenstiel doppelt geschweift  
mit Stahlschutz, doppelt gesichert  
durch Ring-Keilbefestigung  
mit lösem Gummiaufsatz

VPA-G5 tested  
forged head  
ash handle double flared  
double secured with ring wedge  
and plastic flang  
with moveable rubber head

Art.-No.	g	l mm	g	📦
9831000	1000	260	1575	1
9831250	1250	260	1780	1
9831500	1500	300	2105	1
9832000	2000	300	2605	1