



HSS-METAL CIRCULAR SAW BLADES

HSS DMo5

HSS-E-Cobalt



Dimension Ø x Stärke	Teeth and Tothing										
	3	4	5	6	7	8	9	10	12	14	16
200 x 1.8	200	160	130	100		80					
210 x 2.0	210	160		110		80					
225 x 2.0	220	180	140	120		90					
250 x 2.0	240	200	160	128	110	100		80			
250 x 2.5	240	200	160	128	110	100		80			
275 x 2.0	280	220	180	140	120	110		90			
275 x 2.5	280	220	180	140	120	110		90			
275 x 3.0	280	220	180	140	120	110		90			
300 x 2.5		220	180	160	140	120		94			
300 x 3.0		220	180	160	140	120		94			
315 x 2.5		240	200	160	140	120		100	80		
315 x 3.0		240	200	160	140	120		100	80		
325 x 3.0		250	200	170	146	128					
350 x 2.5		280	220	180	160	140	120	110	90		
350 x 3.0		280	220	180	160	140	120	110	90		
360 x 3.5		280	220	180	160	140	120	110	90		
370 x 3.0		280	220	190	160	140	120	110	100		
400 x 3.0			250	200		160		120		96	
400 x 3.5			250	200		160		120		96	
400 x 4.0			250	200		160		120		96	
425 x 3.5			260	220		160		130		96	
425 x 4.0			260	220		160		130		96	
450 x 3.5				230		180		140	120		90
450 x 4.0				230		180		140	120		90
500 x 4.0		390	310	260		200		160			

HSS-SEGMENTED CIRCULAR SAW BLADES

with segments of HSS-DMo5,
precutting and finishing teeth

Ø mm	cutting width/mm	number of segments	teeth per segment							
			2	3	4	5	6	8	10	12
275	3.0	12				w	w	w	w	w
300	3.6									
315	3.6	14			w	w	w	w	w	w
340	3.6									
360	3.6	16			w	w	w	w	w	w
370	3.6	16			w	w	w	w	w	w
400	4.0	16			w	w	w	w	w/o	w/o
425	4.0	18			w	w	w	w	w/o	w/o
450	4.0	18			w	w	w	w	w/o	
460	5.0									
500	5.0	18		w	w	w	w	w/o	w/o	w/o
560	5.0	18			w	w	w	w	w	w/o
630	5.0	20				w	w	w/o	w/o	
630	6.0	20		w	w	w	w	w/o	w/o	
660	5.0	Standard								
660	6.0	Standard								
710	6.0	24		w	w	w	w	w/o	w/o	
760	6.0	24		w	w	w	w	w/o	w/o	
810	6.8	Standard								
910	7.2	Standard								
970	7.8	30			w	w	w	w		
1000	8.0	30				w				
1020	8.3	30	w	w	w	w	w	w/o		
1120	8.5	36	w	w	w	w	w			
1250	9.0	36	w	w	w	w	w	w/o		
1320	9.0	36	w	w	w	w	w	w		
1430	9.5	36	w	w	w	w	w	w/o		

w = with cooling slot w/o = without cooling slot



The hole and secondary hole can be supplied to suit any circular saw machine.

HSS metal circular saw blades are resharpened by sub-contractors and charged according to cost.

Other dimensions available on request.