





CHAVE DINAMOMETRICA DE RELOGIO



CHAVES DINAMOMÉTRICAS DIAL ANALÓGICAS



COD.	AF inch	Nm	Lb.ft	Lb.in	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Kg	
56930	1/4	0-2		0-18			28	50				
56931		0-8		0-70							0,6	
56932	3/8	0-20		0-175	310							
56933		0-50	0-35			26	31		30	38		
56934		0-100	0-70		480			55			0,9	1
56935	1/2	0-200	0-150				45				1	
56936		0-350	0-250		550							
56937	3/4	0-800	0-600		1190	31	55	65			6,5	
56938	1	0-2000	0-1500		1620		60	70	50	65	9,0	


ESPECIFICACIONES TÉCNICAS / TECHNICAL SPECIFICATION / DÉTAILS TECHNIQUES

Precisión / Accuracy / Précision	3%
Certificado de calibración / Calibration certificate / Certificat de calibrage	●
Estuche individual / Individual case / Étui individuel	●

• Certificado de calibración externo ENAC / ENAC external calibration certificate / Certificat de calibrage externe ENAC


* G12: GARANTÍA 12 MESES

CHAVE DINAMOMETRICA DIGITAL PARA CONTROL DE PAR




COD.	AF inch	Nm	Lb.ft	Lb.in	Kg.cm	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Kg
56095	1/4	1,5-30	1-22	13-265	15-306	390	23	19	11			1,4
56096	3/8	6,8-135	5-100	60-1195	69-1378	415	30	27	15			1,5
56097		10-200	7-148	88-1770	102-2041	530				39	44	2,1
56098	1/2	17-340	12-251	150-3009	173-3469	650	41	35	19			2,3

CHAVE DINAMOMETRICA DIGITAL



COD.	AF inch	Nm	Lb.ft	Lb.in	Kg.cm	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Kg
62955	1/4	1.5-30	1-22	13-265	15-306	390	23	19	11			1,4
62956	3/8	6.8-135	5-100	60-1195	69-1378	415	30	27	15			1,5
62957		10-200	7-148	88-1770	102-2041	530						2,1
62958	1/2	17-340	12-251	150-3009	173-3469	650	41	35	19			2,3
62959	1/4	1.5-30	1-22	13-265	15-306	390	23	19	11	39	44	1,7
62960	3/8	6.8-135	5-100	60-1195	69-1378	415	30	27	15			1,9
62961		10-200	7-148	88-1770	102-2041	530						2,5
62962	1/2	17-340	12-251	150-3009	173-3469	650	41	35	19			2,7

CHAVE DINAMOMETRICA MINI REVERSIVEL ANALOGICA




COD.	AF inch	Nm	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Kg
62982	1/4	1-5	185	28	25	15	26	0,35

CHAVE DINAMOMETRICA DIGITAL COM ENVIO DE DADOS



COD.	AF inch	Nm	Lb.ft	Lb.in	Kg.cm	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Kg
67685	3/4	25-500	18,4-368,7	221-4424	255-5102	950	60	55	30	38	38	5,6
67686		42,5-850	31,3-626,8	376-7521	434-8674	1220						6,2
67688	1	75-1500	221-1106	-	-	1800	70	65	35			5,6
67721	3/4	25-500	18,4-368,7	221-4424	255-5102	950	60	55	30	38	38	5,6
67722		42,5-850	31,3-626,8	376-7521	434-8674	1220						6,2
67724		75-1500	221-1106	-	-	1800						70

CHAVE DINAMOMETRICA REVERSIVEL ANALOGICA



COD.	AF inch	Nm	Lb.ft	Lb.in	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Kg	
62951	1/4	2,5-12	-	20-105	290	28	30	19		0,8	
62952		4-20	-	30-180							
65871		-	-	35-180							
62965	3/8	6-30	-	50-250	320	37	40			0,9	
65872		-	-	120-450							
62953		25-125	20-90	-							40
57686	1/2	10-70	-	100-600	440	38	41			0,9	
62954		25-125	20-90	-							25
65873		-	-	350-1800							38
62963	1/2	40-200	30-150	-	460	40	44		38	1,4	
62968		65-335	50-250	-							
65918		-	-	1000-3000							520
62969	3/4	160-800	120-600	-	1040	60	66	39		8,6	
65919		-	-	1000-7200							
62976		200-1000	150-750	-							
62977	1	300-1500	200-1100	-	1250	72	82	40		12	
62978		400-2000	300-1500	-							
62979		600-3000	400-2200	-							

CHAVE DINAMOMETRICA ANALOGICA COM ADAPTADOR 9x12



mm	Nm
9 x 12	2,5-12
	6-30
	25-125

CHAVE DINAMOMETRICA DIGITAL COM ADAPTADOR 14x18



14 x 18

COD.	mm	Nm	Lb.ft	Lb.in	Kg.cm	L (mm)	A (mm)	B (mm)	Kg
57587	14 x 18	10-200	7-148	88-1770	102-2041	470	39	44	1,4
57588		17-340	12-251	150-3009	173-3469	590			1,6
57591		10-200	7-148	88-1770	102-2041	470			1,4
57592		17-340	12-251	150-3009	173-3469	590			1,6