


MAST AMPLIFIERS



MASTIO AML 900 Series

Mast band amplifier specially designed for the reception of DTT signals with optimum quality.

APPLICATION

Suitable for TV / FM signal distribution in individual systems or small installations.

FEATURES

- Small size.
- 100% protected zamak box provides excellent immunity against interference.
- Protected against LTE signals.



MODEL	AML 910 L D2	AML 910 DC D2	AML 920 L D2		AML 920 DC D2		AML 930 DC D2				
Reference	36961	36962	36963			36964		36965			
Nbr. of inputs	1	1	2		2		3				
Bands	UHF 470÷694	UHF 470÷694	BIII 174÷230	UHF 470÷694	BIII 174÷230	UHF 470÷694	BIII 174÷230	UHF 470÷694	UHF 470÷694		
Gain	dB 25	dB 35	dB 20	dB 25	dB 30	dB 35	dB 25	dB 35	dB 35		
Gain regulation	dB					15					
Output level	dBµV					108					
Input/output impedance	Ω					75					
Noise figure	dB 3	dB 3	dB 4		dB 3		dB 4	dB 5	dB 5		
Consumption	mA 60	mA 80	mA 60		mA 80		mA 80				
DC pass	mA -	mA 45	mA -		mA 45		mA -	mA 45	mA 45		
Supply voltage	Voc		24 ± 10%								
Packing dimensions	mm		89 x 97 x 45								
Weight	Kg		0.2								

MAST AMPLIFIER AND POWER SUPPLY KIT

Reference	Model	Composition
36955	AML 910 L D2 K	Mast amplifier and power supply kit (24V, 150mA). 1 UHF input, 25dB gain, 108dB output level.
36956	AML 910 DC D2 K	Mast amplifier and power supply kit (24V, 150mA). 1 UHF input, 35dB gain, 108dB output level.
36958	AML 920 DC D2 K	Mast amplifier and power supply kit (24V, 150mA). 2 inputs, BIII;UHF, 30;35dB gain, 108dB output level.
36959	AML 910 L D2 K	Mast amplifier and power supply kit (24V, 150mA). 2 inputs, BIII;UHF, 25;25dB gain, 108dB output level.
36959	AML 930 DC D2 K	Mast amplifier and power supply kit (24V, 150mA). 3 inputs, BIII, UHF 1, UHF 2, 35dB gain, 108dB output level.