

LOOPWHEELS URBAN

+ DETAILS

The suspension wheel offers supreme comfort and protection against vibrations



Suspension system made in carbon



Customizable in several colours



Compatible with electric propulsion systems



LOOPWHEELS URBAN

+ TECHNICAL DATA

NOTE: In case of divergence between the text and image, the information described in the text shall prevail. In the sense of continuous improvement, Orthos XXI reserves the right to make changes to its products without previous notice. More information available in the product manual.

Loopwheels Urban

Manufacturer: **LOOPWHEELS**

WHEEL SIZE	24" (540 mm) and 25" (559 mm)
ETRTO NUMBER	25 – 540 (24 x 1.00) and 25 – 559 (25 x 1.00)
AXLE BEARING	1/2" (12.7 mm) and 12 mm
HUB	CNC machined aluminium, anodised black sealed cartridge bearings
SPRING/LOOP MATERIALS	carbon fibre composite
LOGO COLOUR	white reflective logos
PUSH RIM	black powder-coated aluminium as standard or upgrade to a more ergonomic option
PUSH RIM OFFSET <small>(distance to wheel rim)</small>	narrow (11 mm) or wide (19 mm)
RIM	double-walled aluminium, black
INNER RIM WIDTH	16 mm
BEARING WIDTH AT FACES	1.8" (45.8 mm)
WHEEL WEIGHT	1.36 kg
MINIMUM USER WEIGHT	35 kg
MAXIMUM LOAD <small>(user and wheelchair)</small>	120 kg
MAXIMUM SPEED	25 km/h

Tolerance: +/- 10 mm

Updated on 05/24