

## Testing tools LAN USB TESTER

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The fully insulated plastic housings of our continuity testers are shockproof and unbreakable, making these instruments ideal for daily use, even in tough conditions. The integrated torch makes it easier to locate defective cables quickly and safely. The results of the continuity test can be conveyed visually and acoustically.

### General ordering data

Type	LAN USB TESTER
Order No.	<a href="#">9205400000</a>
Version	Continuity tester for data cables
GTIN (EAN)	4032248732128
Qty.	1 Stück

## Testing tools LAN USB TESTER

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Width	135 mm	Width (inches)	5,315 inch
Height	27 mm	Height (inches)	1,063 inch
Depth	65 mm	Depth (inches)	2,559 inch
Weight	174 g	Net weight	355 g

### Environmental Product Compliance

REACH SVHC Lead 7439-92-1

### Measuring and testing devices

Display	LED	Protection degree	IP44
Remote box dimensions	65 x 28 x 27 mm	Remote box weight	30 g
Supply	9V battery	Testable cable length, max.	1.000 m
Tested and approved according to	EN/ IEC 61010	Type of connection	RJ45, USB A, USB B

### Classifications

ETIM 3.0	EC000495	ETIM 4.0	EC000069
ETIM 5.0	EC000069	ETIM 6.0	EC002080
UNSPSC	41-11-36-37	eClass 5.1	27-20-11-06
eClass 6.2	27-20-03-01	eClass 7.1	27-20-03-01
eClass 8.1	27-20-03-01	eClass 9.0	27-20-11-08
eClass 9.1	27-20-03-90		

### Approvals

ROHS Conform

### Downloads

Brochure/Catalogue [CAT 9 IETH 18/19 EN](#)  
[CAT 6 TOOLS 15/16 EN](#)

**Datenblatt**

**Testing tools  
LAN USB TESTER**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Zeichnungen**

**Example of use**

