



ZCK D15

Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKM XCKL
Associated body	ZCKM1H29 ZCKM6H7 ZCKMD35 ZCKL1H7 ZCKM5H29 ZCKL8 ZCKLD37 ZCKLD35H7 ZCKM9H29 ZCKL1 ZCKMD37 ZCKM6H29 ZCKMD39 ZCKLD39 ZCKM5H7 ZCKLD39H7 ZCKM1H7 ZCKM8H29 ZCKM7 ZCKL7 ZCKLD35 ZCKMD37H29 ZCKL6H7 ZCKL8H7 ZCKMD39H7 ZCKLD31H7 ZCKL7H7 ZCKLD37H7 ZCKMD31H29 ZCKMD35H29 ZCKM1 ZCKM9

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKMD37H7  
 ZCKM7H29  
 ZCKL5  
 ZCKL6  
 ZCKM8H7  
 ZCKM5  
 ZCKLD31  
 ZCKMD39H29  
 ZCKMD31H7  
 ZCKL5H7  
 ZCKM6  
 ZCKMD31  
 ZCKM8  
 ZCKM7H7  
 ZCKMD35H7

Movement of operating head	Rotary
Type of operator	Roller lever spring return thermoplastic
Type of approach	Lateral approach 2 directions

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

### Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0951 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------