

Product data sheet

Specifications



Wiser Gateway

CCT501901

Main

Range	Wiser
Product or component type	Gateway
Device application	Zigbee/IP network interface

Complementary

Colour	White
Communication network type	Ethernet conforming to IEEE 802.3 WLAN - 2.4 GHz conforming to IEEE 802.11 b/g/n ZigBee - 2.4 GHz conforming to IEEE 802.15.4
Port Ethernet	10/100BASE
Connector type	connector(s)1 x micro USB port female for adaptor connector(s)1 x 2-pin terminal block
Electrical connection	Cable, 0.25...1.5 mm ² (terminal)
[Us] rated supply voltage	5 V DC, <1 A 12 V DC, <0.5 A
Realtime clock	With RTC-battery set
Local signalling	Indicator: 3 LEDs (white)
Width	86 mm
Height	86 mm
Depth	34 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	10...90 %
Environmental characteristic	Indoor use
IP degree of protection	IP20
Standards	EN 62368-1 IEC 62368-1
Product certifications	CE Zigbee 3.0

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	377 g
Package 1 Height	7 cm
Package 1 width	13.5 cm
Package 1 Length	19 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	3.531 kg
Package 2 Height	16.5 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	320
Package 3 Weight	12 kg
Package 3 Height	64.5 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information