





USER TECHNICAL FILE PRODUCT

NAME: <u>SPRINTER</u>	
REFERENCE: <u>1208.10</u>	
FAMILY: <u>WINNER</u>	

PRODUCT DESCRIPTION

CERTIFICATION NORM: <u>EN ISO 20345:2011</u> Additional requirement: <u>IEC 61340-4-3</u>	PROTECTION CATEGORY: <u>S3SRC</u> <u>ESD</u>
PROTECTION TOECAP: <u>STEEL (resistant at impact 200J and compression 15kN)</u>	PROTECTION INSERT: <u>KEVLAR (penetration resistant at 1100N)</u>
SIZES: <u>39 AT 48</u>	COLOUR: <u>BLACK</u>
UPPER RAW MATERIALS: Vamp, tongue, collar: <u>black synthetic regilla seu!</u> Toe: <u>Black matrix Kevlar</u> Quarter, counter: <u>Black leather natur</u>	LINING MATERIALS: <u>BLACK TEXTILE</u>
OUTSOLE: <u>3D: DOUBLE DENSITY PU + RUBBER</u> 	INSOCK: <u>BLACK ANTISTATIC TEXTILE NO RISK</u>

- OTHER CHARACTERISTICS:**
- PU outsole: anti vibration, antistatic, Side stability, resistance at hydrolysis, resistance to fuel oil, energy absorption on seat region; slip resistance at A condition
 - Electric Static Discharge (ESD) – IEC 61340-4-3
 - Textile absorbing lining;
 - Soft tongue;
 - Use for: all year

PRODUCT APLICATIONS:

OUTDOOR _____

INDOOR _____

ESPECIALS _____