



# Mobil Super™ 3000 X1 5W-40

## Premium Full Synthetic Passenger Vehicle Motor Oil

### Product Description

Mobil Super™ 3000 X1 5W-40 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

### Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 3000 X1 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

### Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Mobil Super 3000 X1 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Many engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- High Performance Engines
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

---

**Mobil Super 3000 X1 meets or exceeds the requirements of: 5W-40**

|                   |   |
|-------------------|---|
| ACEA A3/B3, A3/B4 | X |
| API SN/SM         | X |

---

**Mobil Super 3000 X1 has the following builder approvals: 5W-40**

|                   |   |
|-------------------|---|
| MB-Approval 229.3 | X |
| VW 502 00/505 00  | X |

|                                      |   |
|--------------------------------------|---|
| vw 502 00/003 00                     | ^ |
| BMW Longlife-01                      | X |
| Porsche A40                          | X |
| Peugeot/Citroën Automobiles B71 2296 | X |
| Renault RN0710 / RN0700              | X |
| AVTOVAZ (LADA cars) AAE B5           | X |

**Mobil Super 3000 X1 is recommended by ExxonMobil for use in applications requiring: 5W-40**

|                  |   |
|------------------|---|
| API CF           | X |
| Opel GM-LL-B-025 | X |

## Typical Properties

### Mobil Super 3000 X1

|                                  |        |
|----------------------------------|--------|
| Viscosity                        | 5W-40  |
| cSt @ 40°C                       | 84     |
| cSt @ 100°C                      | 14     |
| Sulfated Ash, wt%, ASTM D 874    | 1.1    |
| Phosphorous                      | 0.0095 |
| Flash Point, °C, ASTM D 92       | 222    |
| Density @15° C kg/l, ASTM D 4052 | 0.855  |
| Pour Point, °C, ASTM D 97        | -39    |

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

7-2012

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg

B-2030 Antwerpen, Belgium

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2012 Exxon Mobil Corporation. All rights reserved..