

Diesel Purge

DESCRIPTION

Diesel Purge contains a mixture of agents with powerful cleaning properties. The special additives guarantee corrosion protection and increase ignition performance (cetane number).

PROPERTIES

- cleans fuel systems
- breaks down deposits in injectors
- improves the ignition performance (cetane number) of diesel fuel
- prevents partial-load knocking
- protects against corrosion
- guarantees optimum combustion
- increases operational reliability and economy

TECHNICAL DATA

Basis	: additives dissolved in carrier fluid
Colour	: yellowish/orange, clear
Density at 20 °C	: 0.82 g/cm ³
Flash point	: 63 °C
Regulation on flammable liquids (German)	: A III
Viscosity at 20 °C	: approx. 2.3 mm ² /s
Pour point	: -35 °C

APPLICATION

Used for all diesel engines to prevent and eliminate problems associated with uneven idling and partial-load knocking. Quantity to be used for preventive and remedial use: 500 ml.

INSTRUCTIONS

Preventive use

Add to diesel fuel according to the inspection intervals

Remedial use

Unclip the fuel pipe and immerse the end in the Diesel Flush. Close the fuel return pipe or feed that into the Diesel Purge. Start the engine and allow the engine to run at different speeds with the Diesel Purge unmixed. After the cleaning process, assemble the vehicle's system. In extreme cases, repeat the cleaning procedure if necessary.

As an alternative to remedial procedure, our Jet-Clean Unit can also be used for cleaning. To do this, pour 2-3 litres Diesel Purge into the Jet-Clean tank. Further instructions on use are given in the instructions for the Jet-Clean unit.

AVAILABLE PACK SIZE

Diesel Purge	500 ml	Part no. 2509
	5 Liter	Part no. 2525

PI 01/03/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

