



TotalEnergies

Classic 9 5W-40

KEY DATA



LIGHT VEHICLE RANGE

INTERNATIONAL STANDARDS

- ACEA A3/B4
- API SN/CF

MANUFACTURER APPROVALS ¹

Meets the requirements of the following OEM specifications:

- MB-229.3
- VW 502.00/505.00
- Renault RN 0700/0710

¹ Please refer to car owner's manual

CLASSIC, THE GUARANTEED QUALITY

Synthetic technology lubricant intended for lubrication of gasoline and Diesel light vehicle engines. This high-performance lubricant is specifically developed to ensure compatibility with post-treatment systems.

APPLICATIONS

Specifically developed for Diesel engines: Suitable for all Diesel engines, including the most recent, which comply with Euro V polluting emissions reduction norms in particular.

Post treatment systems: This pollution-control engine oil provides engines with the best possible protection against wear and clogging. The post-treatment systems are also protected over the long-term thanks to the "Low SAPS" formulation (low content of sulphated ash, phosphorus and Sulphur contents).

The most severe journeys. All times of year: Suitable for all journeys (in town, on highways and motorways) and particularly in severe weather conditions.

CUSTOMERS BENEFITS

- Reduced environmental impact: Classic 9 5W-40 is formulated to protect anti-pollution systems such as particulate filter and three-way catalysts. Pollutant emissions such as HC, NOx, CO, Particles are therefore reduced.
- Durability of post-treatments systems: This oil ensures optimum engine longevity with its antiwear properties that protect the engine's most sensitive parts.
- Engine cleanliness : Ensures maximum engine cleanliness thanks to its detergency and dispersion properties.
- Extended oil change intervals: Classic 9 5W-40 satisfies the most demanding manufacturer service plans by permitting extra-long intervals.

CHARACTERISTICS²

TEST	UNIT	RESULT
Viscosity grade	-	5W-40
Kinematic viscosity at 40°C	mm ² /s	88,5
Kinematic viscosity at 100°C	mm ² /s	14,4
Density at 15°C	kg/m ³	853
Viscosity index	-	169
Pour point	°C	-36
OC Flash point	°C	220

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

