



TotalEnergies

# Classic 9 5W-30

## KEY DATA



### LIGHT VEHICLE RANGE

### INTERNATIONAL STANDARDS

- ACEA A5/B5
- API SL/CF

### MANUFACTURER APPROVALS <sup>1</sup>

Meets the requirements of the following OEM specifications:

- Ford WSS-M2C913-D
- Ford WSS-M2C913-C

Suitable for:

- Fiat 9.55535-G1
- Fiat 9.55535-N1

<sup>1</sup> Please refer to car owner's manual

## CLASSIC, THE GUARANTEED QUALITY

Synthetic technology multigrade oil for gasoline and Diesel engines.

## APPLICATIONS

All gasoline/Diesel engines: Developed to cover the most stringent requirements of both recent gasoline and Diesel engines (since MY 2000).

Direct injection Diesel: Particularly suited to turbocharged, multi-valve and direct injection engines.

The most severe journeys. All times of year: Can be used in the most difficult operating conditions (motorways, dense city traffic...), whatever the season.

"Vigorous" driving: For all driving styles, particularly "vigorous" and high speeds.

## CUSTOMERS BENEFITS

- High performance: Excellent engine protection and oxidation resistance.
- Lengthens engine life: Immediate lubrication of engine parts during cold starts, leading to longer engine life.
- Extended oil change intervals: Classic 9 5W-30 meets the requirements of the manufacturers as regards extended oil change intervals.

## CHARACTERISTICS<sup>2</sup>

TEST	UNIT	RESULT
Viscosity grade	-	5W-30
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	57
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	9.9
Density at 15°C	kg/m <sup>3</sup>	853
Viscosity index	-	170
Pour point	°C	-36
OC Flash point	°C	224

<sup>2</sup> The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubricants / Last update of this datasheet: July 22 / Classic 9 5W-30

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at [www.lubricants.totalenergies.com](http://www.lubricants.totalenergies.com).