



Castrol Power 1 Racing 4T 5W-40

Co-Engineered with BMW Motorrad*

Description

Castrol Power 1 Racing 4T 5W-40 is fully synthetic 4-stroke engine oil for modern high performance sports bikes that increases engine acceleration and power right up to max rpm.

Its Race Derived Technology based on Castrol's racing history and testing experience ensures maximum engine performance without sacrificing engine durability thus giving a significant benefit over other types of engine oils.

Castrol Power 1 Racing 4T 5W-40's formula employs the very latest Trizone Technology™ for 4-stroke motorcycles, so as to give optimum protection of the engine, clutch and gears even under the most arduous riding conditions including sustained operation at high rpm.

Application

Castrol Power 1 Racing 4T 5W-40 is suitable for all modern high performance motorcycle engines where API and or JASO specifications are recommended. It is specially approved by BMW for K1600, K1300, K1200 models, S1000 RR, G450X. It can be used in several motorcycle gearboxes, where delivers excellent clutch performance.

Advantages

- Ultimate performance in extreme riding – oil flows fast and stays strong, reducing internal engine friction
- Tested and proven to deliver exceptional acceleration at the touch of the throttle
- Fully synthetic 4-stroke motorcycle engine oil featuring Trizone Technology™
- Race Derived Technology for max engine acceleration.
- Extreme high temperature air-cooled and water-cooled engine performance.
- Excellent high speed oil consumption control and volatility.
- Excellent shear stability to prevent viscosity break down.
- Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	77.2
Viscosity Index	ASTM D2270	None	171
Pour Point	ASTM D97	°C	- 39
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.4
Flash Point, PMCC	ASTM D93	°C	200

Product Performance Claims

API SL

JASO MA-2

BMW S1000RR, K1200, K1300, K1600, R1200 (K50), HP4, G450 and C1

Kawasaki KX250/450F

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Power 1 Racing 4T 5W-40

13 Feb 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire, SN3 1RE, Castrol (Ireland), Castrol Ireland Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire, SN3 1RE

Castrol UK Telephone: 01793 512712 Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125 Castrol Ireland Telephone: +44 (0)1793

512712 Automotive Technical Helpline: 1800 509 353 Orders/Enquiries: 1850 930 394

www.castrol.com/uk

Page 2 of 2