



# Castrol Power 1 Racing 4T 10W-40

Race Derived Technology

#### Description

Castrol Power 1 Racing 4T is fully synthetic engine oil for modern, high performance 4-stroke sports bike that increases engine acceleration and power right up to maximum rpm.

Castrol Power 1 racing 4t using "Race Derived Technology" based on Castrol's long and successful racing association, flows fast and stays strong, reducing internal engine friction even under the most arduous riding conditions.

It has been tested and proven to deliver exceptional acceleration and power at the touch of the throttle.

The added Castrol advantage of Trizone Technology<sup>™</sup> ensures uncompromised performance protection, its ultimate performance for extreme riding.

### Application

Castrol Power 1 Racing 4T is designed for high performance 4-stroke sports bikes to deliver optimum power and protection in all riding conditions.

It is suitable for all makes of 4-strokes bikes, both carburettor and fuel injected where API SL (and below) and JASO MA or MA2 specifications are recommended.

#### **Advantages**

- Ultimate performance in extreme riding oil flows fast and stays strong, reducing internal engine friction
- Tested and proven to deliver exceptional acceleration at the touch of the throttle
- Fully synthetic 4-stroke motorcycle engine oil with Trizone protection of engine, clutch and gears
- Complies with requirements of catalyst equipped engines

## **Typical Characteristics**

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	Report
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm²/s	13.0
Viscosity, Kinematic 40C	ASTM D445	mm²/s	83
Viscosity Index	ASTM D2270	None	160
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	5000
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.8

#### **Product Performance Claims**

API SL JASO MA-2 Recommended by Triumph for all four stroke models

#### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Ltd, Wakefield House, Pipers Way, Swindon, SN3 1RE, UK

www.castrol.com